



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : D21F 1/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/37272</p> <p>(43) International Publication Date: 27 August 1998 (27.08.98)</p>
<p>(21) International Application Number: PCT/GB98/00361</p> <p>(22) International Filing Date: 18 February 1998 (18.02.98)</p> <p>(30) Priority Data: 9703297.3 18 February 1997 (18.02.97) GB</p> <p>(71) Applicant (for all designated States except US): SCAPA GROUP PLC [GB/GB]; Oakfield House, 93 Preston New Road, Blackburn BB2 6AY (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): HOLDEN, David [GB/GB]; 147 Lammack Road, Blackburn BB1 8LA (GB).</p> <p>(74) Agents: GOODWIN, Mark et al.; Wilson Gunn M'Caw, 41-51 Royal Exchange, Cross Street, Manchester M2 7BD (GB).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: MODIFIED SPIRAL SEAM ARRANGEMENT</p> <div data-bbox="337 1102 1299 1354" data-label="Image"> </div> <p>(57) Abstract</p> <p>A seam arrangement for connecting the two ends of a fabric so as to form an endless belt, particularly for use in papermaking. The seam arrangement comprises two endless coils (10) which are respectively located at the free ends of the fabric and on interdigitation are brought into union by a pindle wire. Each loop of the coils (10) is secured to the fabric by a "short" fabric loop (22) and a "long" fabric loop (18). The short fabric loop is located at the right hand side of the long fabric loop when looking up the fabric towards the seam.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

-1-

MODIFIED SPIRAL SEAM ARRANGEMENT

This invention relates to a modified spiral seam arrangement.

Spiral seams are used for example to connect the ends of fabrics to form endless belts for use in paper machine clothing, especially press felt base cloths or dryer fabrics.

In a spiral seam, the ends of a fabric are provided at each edge to be formed with a loop structure capable of interdigitating with a corresponding loop structure on the opposite edge, and the seam is usually secured by means of a pintle wire or rod extending axially through the interdigitated loops. Conveniently, the loops are provided by means of a pair of, preferably flattened, helical coils, each formed from a single continuous metal wire, plastic coated wire, or suitable plastic monofilament. The helical coils are woven into the fabric, or otherwise secured depending upon the nature of the substrate. One side of the spiral is substantially flatter than the other so that the loops are substantially D shaped, the flatter sides being directed towards the paper supporting surface of the fabric in plan view, from the more curved side, each loop of the spiral has an N-shape.

Machine direction (MD) warp yarns are woven in repeat groups of four to each turn of the helical coil. Alternate yarns run short, and the remaining two spaced yarns extend into the fringed seam area and are looped around the leg of the coil adjacent the seam, and a return portion of each is back woven into the fabric in the space made available by the yarns which have run short to in effect provide a continuous warp path.

The weave pattern is such that one of the MD yarns forms a "long" fabric loop, floated over at least the last cross machine weft yarn, and the other a "short" fabric

-2-

loop coming from below the last weft yarn or floated over fewer yarns than the "long" fabric loop. In the known fabric seam the "short" fabric loop lies between the diagonal and the left hand vertical limb of the N-shape of the spiral coil loop. In this arrangement the "short" fabric loop distorts the coil loop to such an extent that part of the seam moves proud of the belt. This results in undesirable marking of the paper which is being manufactured on the belt.

According to the present invention there is provided a seam arrangement for connecting the ends of a fabric so as to form an endless belt, the seam arrangement comprising a first coil provided at one of said ends of the fabric and a second coil provided at the other of said ends of the fabric, wherein the two coils are operable to be interdigitated and secured together by means of a pintle wire which may be passed through the interdigitated coil loops, and wherein two machine direction yarns of the fabric are passed through each loop of a coil so as to secure the coil to the fabric edge, the machine direction yarns associated with each coil loop providing a "long" fabric loop and a "short" fabric loop, wherein each coil loop notionally forms an N-shape with the top of the N-shape being provided by the free ends of the coil loop which are remote from the fabric end to which that coil loop is secured, characterised in that the "short" fabric loop lies between the diagonal and the right hand limb of the N-shape of the spiral coil loop.

Space for back-weaving the MD yarns is created by terminating selected MD yarns short of the edge region, at a joining point, and the return portions back woven to the joining point so that there is no perceptible break in the weave. The MD yarns would preferably be warp yarns.

It has been found that an arrangement of this kind allows the spiral coil to be

seated closer into the plane of the fabric, so that the coil stands less proud and thus reduces the extent or depth of any embossing or marking inflicted by the coil on paper which is supported on the fabric and the less proud configuration of the seam makes it less prone to wear.

An embodiment of the invention will now be briefly described with reference to the accompanying drawings wherein:-

Fig.1 is a sectional weave diagram of a seam of a known form of helical seam;

Fig.2 is a diagrammatic plan view showing the weave of the seam of fig.1 from above;

Fig.3 is a diagram corresponding to Fig.1 showing the weave of a seam according to the invention; and

Fig.4 is a diagrammatic plan view, similar to fig.2 of the seam of fig.3.

In a prior art spiral seam, as illustrated diagrammatically in figs. 1 and 2, a flattened helical coil member 10 has a large number of turns, each having a leg 11, alongside the edge of the woven fabric. The coil 10 is flatter on its upperside 10a, than on its lower side 10b, thus providing a 'D' shaped outline. In plan (as seen from fig.2) each loop has the shape of an 'N' with the lower side parts 10b forming the diagonal of the N-shape. In the example, the fabric comprises two layers of cross-machine direction weft yarns, 12, with an upper layer and a lower layer of staggered yarns. Machine direction warp yarns 14 are woven through the weft yarns 12 in a pattern wherein each warp yarn floats over two weft yarns in the upper layer, and passes under one weft yarn in the lower layer in each repeat.

The seam is formed with two MD yarns for each turn of the coil member 10, a first MD yarn 16, shown in fig.1 as a continuous double line, has a main part 19 which

-4-

forms a "long" fabric loop 18, over the last two upper layer cross-machine yarns and under and around the leg 11 of the coil adjacent the fabric edge. The yarns nest in the 'V' between the nearer end of each coil upper side 10a and lower side 10b, with the "short" fabric loop 22 nesting on the apex of the 'V' and the "long" fabric loop 18 further out on the part 10b. The return section 17 of the MD yarn 16 passes over the leg 11, and then passes over the upper yarn adjacent the seam, and is back woven into the fabric for a few repeats. The weave space is filled by a normal MD yarn, which is cut short to terminate adjacent the woven back end of section 17. (This is not shown in the drawings).

A second MD yarn 20 has a main part 21 which forms a "short" fabric loop 22, as it emerges from below the last bottom layer cross-machine yarn and below the last upper layer yarn to pass under and around the leg 11, adjacent the "long" fabric loop 18. After it passes about the leg 11 of the spiral yarn 20 forms a return portion 23 which passes over the last cross-machine yarn and is then woven back into the fabric for several repeats. As with the woven-back end 19 of yarn 16, the space for this is provided by cutting short a normal MD yarn.

As can best be seen from fig.2, the return portions 17, 23 of yarns 16, 20 are located alternately with the main portions, the sequence from top to bottom of the figure being:- main part 21 of yarn 20 (short fabric loop); - return part 23 of yarn 20; - main part 19 of yarn 16 (long fabric loop); - return part 17 of yarn 16.

The fabric loops 18,22 pass about the lower part 10b of the spiral.

It can be seen from fig.2 that the "short" fabric loop distorts the N-shape of the coil loop, forcing the diagonal 11 upwards in a direction perpendicular to the plane of the fabric, resulting in a proud seam. When viewed from above the N-shape can be

seen to be significantly distorted. The "long" fabric loop is consequently less tightly bound around the diagonal and consequently it contributes less to seam strength.

Figs. 3 and 4 illustrate the weave pattern of a spiral seam arrangement according to the invention. The arrangement of cross-machine direction weft yarns 32 is the same as that of fig. 1 - upper and lower layers with the yarns staggered, and a helical coil member 30 which is of the same configuration as that of fig. 1 with more flattened upper parts 30a and more bowed lower parts 30b, appearing in plan view as an 'N' shape. The machine direction warp yarns 34 are again woven through the weft yarns 32 in a pattern wherein each warp yarn floats over two weft yarns in the upper layer, and passes below one weft yarn in the lower layer in each repeat.

The seam is formed with two MD warp yarns for each turn of the coil member 30. A first MD yarn 36, shown in fig. 3 is a continuous double line, has a main part 39 which forms a "short" fabric loop 38, passing below the last cross-machine yarn of the upper layer and under the last cross-machine yarn of the lower layer, about the part 30b, and then returns below the last two cross-machine yarns of the upper layer, to form a return portion 41 which is back woven into the fabric for several repeats. The weave space is created by ending a normal MD yarn to terminate in a joining zone with the end of woven-back portion 41. (This is not shown in the drawing).

A second MD yarn 40 is shown in fig. 3 as a dashed broken line, and has a main part 43 which forms a "long" fabric loop 42 which passes over the last two upper layer cross-machine yarns, about the part 30b of the coil, and passes over the coil, to form a return portion 41, which passes over the last cross-machine yarn, to be woven back into the fabric for several repeats.

As fig. 4 shows, the arrangement of the main and return yarn portions is

different from that shown in fig.2.

The fig 4 arrangement in practice has the effect that the spiral is less distorted by its connection with the fabric ends and is seated better into the plane of the fabric, thus reducing marking of any paper supported on the fabric. The seam stands less proud and is also less prone to wear than previous seams. The seam achieves a far stronger seam with respect to the length direction of the fabric and the coil is less prone to rotating, so that interdigitation of the two opposed loop structures during fabric seaming is made easier.

It is to be understood that the embodiment described with reference to figs.3 and 4 is by way of illustration only. Many modifications and variations are possible.

CLAIMS

1. A seam arrangement for connecting the ends of a fabric so as to form an endless belt, the seam arrangement comprising a first coil provided at one of said ends of the fabric and a second coil provided at the other of said ends of the fabric, wherein the two coils are operable to be interdigitated and secured together by means of a pintle wire which may be passed through the interdigitated coil loops, and wherein two machine direction yarns of the fabric are passed through each loop of coil so as to secure the coil to the fabric edge, the machine direction yarns associated with each coil loop providing a "long" fabric loop and a "short" fabric loop, wherein each coil loop notionally forms an N-shape with the top of the N-shape being provided by the free ends of the coil loop which are remote from the fabric end to which that coil loop is secured, characterised in that the "short" fabric loop lies between the diagonal and the right hand limb of the N-shape of the spiral coil loop.
2. A modified spiral seam arrangement as claimed in claim 1, wherein a number of machine direction yarns are terminated short of the edge region, at a joining point, and the return portion back woven to the joining point.




Fig. 1 (Prior Art)




Fig. 2 (Prior Art)




Fig. 3




Fig. 4

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/00361

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 021F1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 021F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 12 51 105 B (HEINZ KERBER) 28 September 1967 -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *S* document member of the same patent family

Date of the actual completion of the international search

15 June 1998

Date of mailing of the international search report

25/06/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3018

Authorized officer

De Rijck, F

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/00361

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 1251105	B	NONE	

Form PCT/ISA/210 (patent family annex) (July 1992)

PUB-NO: WO009837272A1

DOCUMENT-IDENTIFIER: WO 9837272 A1

TITLE: MODIFIED SPIRAL SEAM ARRANGEMENT

PUBN-DATE: August 27, 1998

INVENTOR-INFORMATION:

NAME	COUNTRY
HOLDEN, DAVID	GB

INT-CL (IPC): D21F001/00

EUR-CL (EPC): D21F001/00

ABSTRACT:

CHG DATE=19990905 STATUS=O>A seam arrangement for connecting the two ends of a fabric so as to form an endless belt, particularly for use in papermaking. The seam arrangement comprises two endless coils (10) which are respectively located at the free ends of the fabric and on interdigitation are brought into union by a pintle wire. Each loop of the coils (10) is secured to the fabric by a "short" fabric loop (22) and a "long" fabric loop (18). The short fabric loop is located at the right hand side of the long fabric loop when looking up the fabric towards the seam.

———— KWIC ————

Abstract Text - FPAR (1):

CHG DATE=19990905 STATUS=O>A seam arrangement for connecting the two ends of a fabric so as to form an endless belt, particularly for use in papermaking. The seam arrangement comprises two endless coils (10) which are respectively located at the free ends of the fabric and on interdigitation are brought into union by a pintle wire. Each loop of the coils (10) is secured to the fabric by a "short" fabric loop (22) and a "long" fabric loop (18). The short fabric loop is located at the right hand side of the long fabric loop when looking up the fabric towards the seam.

Title of Patent Publication - TTL (1):

MODIFIED SPIRAL SEAM ARRANGEMENT